

# Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012

This report is intended to help you identify where the biggest opportunities exist to improve the environmental performance of your assembly. For each environmental indicator, there is a summary for all parts analyzed. There is also a detailed breakdown that reveals the parts that are currently contributing most to the eco impact of your assembly.

## Contents

Energy usage summary .....	page 2
CO2 footprint summary .....	page 3
RoHS compliance and Food-contact compatibility summary .....	page 4
End of life summary.....	page 5
Energy usage: breakdown for the highest-contributing parts .....	page 6
CO2 footprint: breakdown for the highest-contributing parts .....	page 8
Water usage: breakdown for the highest-contributing parts .....	page 10
Cost: breakdown for the highest-contributing parts .....	page 11
How to improve this analysis .....	page 12
Appendix A: How are these figures calculated ? .....	page 13
Appendix B: Waste Hierarchy .....	page 14

### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.


# Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012



## Energy usage: summary for 19 parts analyzed



	Energy (MJ)	Percentages
Material	1700	390 %
Manufacture	35	8 %
Transport	Available in Full Version of Eco Materials Adviser	
Use	Available in Full Version of Eco Materials Adviser	
End of life	-1300	-300 %
Total	440	100 %

### Notes:


- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

# Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012

## CO2 footprint: summary for 19 parts analyzed



	CO2 (kg)	Percentages
Material	110	310 %
Manufacture	2.6	8 %
Transport	Available in Full Version of Eco Materials Adviser	
Use	Available in Full Version of Eco Materials Adviser	
End of life	-75	-220 %
Total	34	100 %

### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012

## RoHS RoHS compliance and Food-contact compatibility: summary for 19 parts analyzed

	RoHS	Food
Compliant or compatible parts	19	13
Non-compliant or non-compatible parts	0	3
Conditions apply, status unknown or no material assigned	0	3
Total	19	19

### Important:

A material that is described as 'non-compliant' with the RoHS Directive or 'non-compatible' for food contact applications means that the material is likely to contain substances that: are restricted under the RoHS Directive; or make the material unsuitable for food contact applications, respectively. By default, parts with no material assigned are also assumed to be RoHS non-compliant and food contact non-compatible. See the 'How to improve this analysis' section for details of which parts have no material assigned.

If a material is described as RoHS Directive 'compliant' or food contact 'compatible', it means that there are commercial grades of that material available which are RoHS Directive compliant or suitable for food contact applications respectively.

It is the responsibility of the user to determine the status of the specific material grades used with regard to RoHS Directive compliance and food-contact compatibility.

### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

 End of life: summary for 19 parts analyzed

	Number of parts
Reuse	0
Recycle	12
Downcycle	1
Combustion	6
Landfill	0
No material assigned	0
Total	19

**Definitions of end of life strategies:**

<b>Reuse</b>	Redistribution of a product to a consumer sector that is willing to accept it in its used state, either for its original purpose or for a different one.
<b>Recycle</b>	(Also called closed-loop recycling.) Reprocessing of recovered materials at the end of product life, returning them to the supply chain as a material of similar type, with similar performance and embodied energy.
<b>Downcycle</b>	(Also called open-loop recycling.) Reprocessing of recovered materials at the end of product life, returning them to the supply chain as a material with lower performance and lower embodied energy. For example: conversion of PET bottles into fibers for fleece clothing; crushing of materials into aggregate or filler replacement.
<b>Combustion</b>	Recovery of a proportion of embodied energy (in the form of heat) by controlled combustion.
<b>Landfill</b>	Disposal of a product by committing it to landfill.

## Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.



## Energy usage: breakdown for the highest-contributing parts

### Energy: Material - breakdown by part

	Energy (MJ)	Percentages
Frame, Door:2	1100	65 %
Hinge, Lower:2	300	18 %
Panel, Door:1	97	6 %
PK46.51.11.015:1	57	3 %
Hinge, Upper:2	43	2 %
Remaining parts	100	6 %
Total	1700	100 %

### Energy: Manufacture - breakdown by part

	Energy (MJ)	Percentages
PK46.51.11.015:1	25	73 %
integral hinge:1	4.2	12 %
integral hinge:2	4.2	12 %
PK46.51.13.003:1	0.36	1 %
PK46.51.13.003:2	0.36	1 %
Remaining parts	0.36	1 %
Total	35	100 %

#### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012

### Energy: End of life - breakdown by part

	Energy (MJ)	Percentages
rubber ring:1	-0.073	0 %
rubber ring:2	-0.073	0 %
rubber ring:5	-0.073	0 %
rubber ring:6	-0.073	0 %
rubber ring:3	-0.073	0 %
Remaining parts	-1300	100 %
Total	-1300	100 %

#### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## CO2 footprint: breakdown for the highest-contributing parts

### CO2: Material - breakdown by part

	CO2 (kg)	Percentages
Frame, Door:2	69	65 %
Hinge, Lower:2	18	17 %
Panel, Door:1	7.0	7 %
PK46.51.11.015:1	3.9	4 %
Hinge, Upper:2	2.6	2 %
Remaining parts	6.4	6 %
Total	110	100 %

### CO2: Manufacture - breakdown by part

	CO2 (kg)	Percentages
PK46.51.11.015:1	1.9	73 %
integral hinge:1	0.31	12 %
integral hinge:2	0.31	12 %
PK46.51.13.003:1	0.027	1 %
PK46.51.13.003:2	0.027	1 %
Remaining parts	0.027	1 %
Total	2.6	100 %

#### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012

### CO2: End of life - breakdown by part

	CO2 (kg)	Percentages
rubber ring:1	0.028	0 %
rubber ring:2	0.028	0 %
rubber ring:5	0.028	0 %
rubber ring:6	0.028	0 %
rubber ring:3	0.028	0 %
Remaining parts	-76	100 %
Total	-75	100 %

#### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012

### Water usage: breakdown for the highest-contributing parts

#### Water: Material - breakdown by part

	Water (liters)	Percentages
Frame, Door:2	6400	86 %
Hinge, Lower:2	480	6 %
Panel, Door:1	130	2 %
PK46.51.11.040:2	110	2 %
PK46.51.11.015:1	98	1 %
Remaining parts	250	3 %
Total	7500	100 %

#### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## Eco Materials Adviser: Opportunity Report

Part/Assembly number: Assy, Door  
Conducted by: miread@grantadesign.com

Date: 10/15/2012

### Cost: breakdown for the highest-contributing parts

#### Cost: Material - breakdown by part

	Cost (USD)	Percentages
Frame, Door:2	17	30 %
Hinge, Lower:2	17	30 %
Panel, Door:1	14	26 %
Hinge, Upper:2	2.4	4 %
PK46.51.11.015:1	1.3	2 %
Remaining parts	4.1	7 %
Total	55	100 %

#### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## To improve the accuracy of your analysis, please address the following issues:

- i** No process assigned to Frame, Door:2.
- i** No process assigned to PK46.51.11.040:2.
- i** No process assigned to 2108-6105015:2.
- i** No process assigned to Panel, Door:1.
- i** No process assigned to Hinge, Upper:2.
- i** No process assigned to Hinge, Lower:2.
- i** No process assigned to Handle, Door:1.
- i** No process assigned to rubber ring:1.
- i** No process assigned to rubber ring:2.
- i** No process assigned to rubber ring:5.
- i** No process assigned to rubber ring:6.
- i** No process assigned to rubber ring:3.
- i** No process assigned to rubber ring:4.

### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## Appendix A: How are these figures calculated?


The environmental indicators included in this analysis are based on detailed, quantitative studies of the natural resources and energy required to:

- produce a material,
- process that material in manufacturing operations,
- manage that material at the end of its useful life.

These studies allow us to say how much energy is consumed or how much CO<sub>2</sub> is released into the atmosphere in order to produce, process and manage 1kg of a material.

The base version of the Eco Materials Adviser focuses on the analysis of the material production, product manufacture and end of life phases of the product lifecycle. The full version extends this analysis to include the eco impacts associated with the transport and use phases.

For each material in the database a default end of life strategy has been assigned (recycle, landfill etc.) based on the most common strategy employed in industrial practice today. Where the end of life phase is shown as reducing the eco impact, this is due to the environmental benefits of avoiding the production of virgin materials (or fuel, in the case of combustion with heat recovery). Further explanation of these calculations and the extensive range of data sources can be found in the 'Eco Impact analysis' section of your user guide.




### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.

## Appendix B: The Waste Hierarchy

The principle of the waste hierarchy is to prioritise End of Life (EoL) strategies towards the top of the hierarchy, such as 'reduce' and 'reuse', which help to retain the value and quality of materials, over strategies such as 'combust' and 'landfill' where material value is lost. Note that 'Design out waste' is not an EoL strategy as such but a design principle - look for opportunities to reduce the amount of material used throughout the product lifecycle.

It is important to note that the appropriate EoL strategy for an assembly is not simply determined by the EoL strategy proposed for the constituent parts. This is because the selection of an appropriate EoL strategy for an assembly will also depend on factors such as the methods used to join materials, the structure of the product and the need for certain parts to be treated separately to comply with legislative requirements (e.g. WEEE Directive). For instance, even if all parts of a product are listed as recyclable, this does not necessarily mean that the assembly can be recycled.



Like Eco Materials Adviser? Upgrade to the full version which:

- Has no limit on the number of parts in your assembly
- Features a more comprehensive materials database of around 3,000 materials
- Analyses the full product lifecycle, including transport and use phases

Upgrade now at: <http://inventor.grantadesign.com/en/upgrade.asp>

### Notes:

- If your assembly exceeds 20 parts, then only the first 20 parts are included in this analysis
- For information on how these figures are calculated, and how to interpret them, please see the appendices at the end of this report.